







Standard Size

Plug

Unit:mm



Socket



Connector Specifications

Product Map (Male)								
Product Map (Female)								
Number of Pins	2pin	3pin	4pin	5pin	7pin	9pin	12pin	14pin
Rated Current	20A			10A		5A		
Working Voltage	300V			300V		250V		
Withstanding Voltage	1500V			1500V		1500V		
Contact Resistance Max	1.0mΩ			3.0mΩ		5.0mΩ		
Insulation Resistance Min	500MΩ			500MΩ		500MΩ		
Contact Diameter x Number	φ2.7x2	φ2.7x3	φ2.7x4	φ1.8x5	φ1.8x7	φ1.0x9	φ1.0x12	φ1.0x14
Wire Gauge	2.5~4.0mm ² /14~12AWG			1.0~1.5mm ² /18~16AWG		0.34~0.5mm ² /22~20AWG		
Cable O.D Range	φ10.0-φ12.0mm			φ10.0-φ12.0mm		φ5.0~6.5mm		
Connection Method	Soldering/Screwing		Soldering					
Protection Level	IP68 (mated, 2m/48h)							
Mechanical Life	Over 2000 Times							
Operating Temperature	-40℃ ~+120℃							
Salt Spray	≥48H							
Certifications	TUV, UL,CE, RoHS							